



SBR2M
Security Camera Tester Borescope 2M (6.5ft)
8mm Diameter



CE

Introduction

Congratulations on your purchase of the Triplet SBR2M Security Camera Tester Borescope. This borescope paired with any security camera tester adds a borescope function to your security camera tester.

Features

- Waterproof (IP67) 8mm camera (Lens only)
- 2m cable (6.5ft)
- 6 adjustable LEDs with thumbwheel control
- Power provided by the camera tester (12V 1/2/3A) — no batteries needed
- Connection cables already included with your camera tester
- Utilizes the display resolution of your camera tester
- Image snapshot and Video record functions dependent on camera tester capability

Safety

This product is designed for industrial inspection camera.

- Avoid severe hits to the camera probe, and do not aggressively pull the cable.
- Please do not use it under high temperature, high magnetic environments or under strong light.
- Do not expose this product to extremely low or high temperatures
- If used for extended periods of time, please take out of the Alkaline battery from the device.
- Do not wipe the unit with corrosive chemical wash.

NOTICE:



WARNING ! This product is an industrial inspection camera and is not intended for medical use or human examination.

Operation

1. Locate the gender changing cables (for BNC and Power) supplied with your security camera accessory kit.
2. Install onto the SBR2M.
3. Connect to BNC Video IN and 12/1,2 or 3A Power output on the security camera tester.
4. Click on Auto HD and the video will be displayed.
5. Follow instruction for taking images and video as you would on your model camera tester.

****Note: The image below is for Reference Only – The SBR2M is shown being paired up with the Tripplett 8150 CAMVIEW IP PRO 5" FULL TOUCH SCREEN 8MP HIGH RESOLUTION SECURITY CAMERA****

Part Number – 8150-BR-Kit includes (1) SBR2M and (1) 8150.



Specifications

	SBR2M
Camera	8mm
Field of View	60°
Depth of View	1.2 to 4" (3 to 10cm)
Cable Length	2m (6.5ft)
Resolution	640 x 480
Illumination	6 adjustable LEDs
Still Image Capture	dependent on camera tester
Video Recording	dependent on camera tester
Power	12V 1/2/3A (provided by camera tester)
Interface	BNC
Dimensions	Camera & Cable: 6.5ft x 0.3" (2m x 8mm) LED Thumbwheel: 2x0.5x0.25" (51x13x6.4mm)
Weight	5.6oz (159g)

Warranty

Triplet / Jewell Instruments extends the following warranty to the original purchaser of these goods for use. Triplet warrants to the original purchaser for use that the products sold by it will be free from defects in workmanship and material for a period of (1) one year from the date of purchase. This warranty does not apply to any of our products which have been repaired or altered by unauthorized persons in any way or purchased from unauthorized distributors so as, in our sole judgment, to injure their stability or reliability, or which have been subject to misuse, abuse, misapplication, negligence, accident or which have had the serial numbers altered, defaced, or removed. Accessories, including batteries are not covered by this warranty

Copyright © 2022 Triplet