# **ONSET**

## HOBO® SD-VOLT-xx Sensor

### Self-Describing DC Voltage Input Cable

For use with HOBO MX1104 and MX1105 multi-channel data loggers, this DC voltage input cable offers integrated strain relief to keep it connected to the logger, and it features Self-Describing technology to automatically communicate configuration information to the logger.



#### **Key Advantages:**

- Self-Describing technology for quick, easy setup
- · Locking jack to ensure cable is connected and stays connected
- Measurement range:
  - o to 2.5 V (w/ SD-VOLT-2.5)
  - 0 to 5 V (w/ SD-VOLT-05)
  - ∘ 0 to 10 V (w/ SD-VOLT-10)
  - 0 to 24 V (w/ SD-VOLT-24)
- Accuracy:
  - ±0.1 mV ±0.1% of reading (w/ SD-VOLT-2.5)
  - ±0.2 mV ±0.3% of reading (w/ SD-VOLT-05)
  - $\circ~\pm 0.4$  mV  $\pm 0.3\%$  of reading (w/ SD-VOLT-10)
  - $\circ~\pm 1.0~\text{mV}~\pm 0.3\%$  of reading (w/ SD-VOLT-24)
- Cable length: 1.8 m (6 ft)

### **HOBO SD-VOLT-xx Sensor Specifications**

	SD-VOLT-2.5	SD-VOLT-05	SD-VOLT-10	SD-VOLT-24
Maximum Inpu	ut0 to 2.5 VDC	0 to 5 VDC	0 to 10 VDC	0 to 24 VDC
Accuracy	±0.1 mV ±0.1% of reading	±0.2 mV ±0.3% of reading	g±0.4 mV ±0.3% of reading	±1.0 mV ±0.3% of reading
Impedance	> 1 M	20 K	20 K	48 K
Resolution	0.002% of full scale			

Cable Length 1.83 m (6 ft)