


Connector Accessories

For Standard Size Connectors

OSTW-SC-T
shown



Connector
sold separately.

GST-SC-K
shown

Wire Caddy (Spool Cap)

Model No.	Compatible Connectors
OSTW-SC-(*)	USTW, OSTW, HSTW
GST-SC-(*)	GST

*Insert thermocouple calibration: **J, K, T, E, R/S, N** or **U** (Uncompensated)

DX-BRLK
dual element
tube clamp.



X-BRLK
tube clamp.



Tube Clamps (Single and Dual Element)


Model No.	Compatible Connectors
X-BRLK-(*)	USTW, OSTW, OGP, GST, HSTW, HGST, OTP
DX-BRLK-(*)	USTW, OSTW, OGP, HSTW

*Insert probe diameter: "116" for 1/16", "18" for 1/8", "316" for 3/16", or "14" for 1/4"

Ordering Examples: X-BRLK-14, tube clamp for 1/4" probes.

DX-BRLK-14, dual tube clamp for 1/4" probes.

SSRT-316-10




Standard Strain Relief Tubing

Model No.	Compatible Connectors
SSRT-316-(*)	OST, OSTW, HSTW, USTW, OGP, OTP, GST, HGST, DTC
SSRT-18-(*)	
SSRT-332-(*)	

*Insert pkg quantity: Select from 5, 10, 50, 100

Center number denotes tubing inside diameter: "316" for 3/16", "18" for 1/8", "332" for 3/32"

PCLM cable clamp.



Cable Clamps

Model No.	Compatible Connectors
PCLM	USTW, OSTW, OGP, HSTW, OTP
PCLM-DTC	DTC
PCLM-GST	GST, HGST

Ferrite Core Cable Clamps

Model No.	Compatible Connectors
PCLM-FT	OSTW, HSTW, OGP, HGST, GST, OTP

SFCL safety clip.




Safety Clips

Model No.	Compatible Connectors
SFCL	USTW, OSTW, OGP, GST, HSTW, HGST

RSACL round
hole panel
mounting
bracket.



SACL panel
mounting bracket.



⚙ Mounting holes
34.9 mm (1.375").
Requires 3.8 mm
(0.150") clearance
holes in panel.

Round Hole Panel Mounting Brackets

Model No.	Compatible Connectors
RSACL	USTW, OSTW, OGP, GST, HSTW, HGST

Panel Mounting Brackets

Model No.	Compatible Connectors
SACL	USTW, OSTW, OGP, GST, HSTW, HGST
TACL	OTP




Connector Accessories



Rubber Boot – SRB
Rated to 95°C (203°F)
SRBS Rated to 230°C (446°F)

Rubber Boots

Model No.	Compatible Connectors
SRB	USTW, OSTW, OGP, HSTW
SRBS	USTW, OSTW, OGP, HSTW



Crimp Style
Brass or SS
Bushing also
available



Crimp Style Bushing

To Order

Model Number	Style Type	Dia A-ID mm (inch)	Dia B mm (inch)	Dia C-OD mm (inch)	Dia D mm (inch)	Dia E mm (inch)	Compatible Connectors
(*)B-OST-CR1.5MM-(**)	1	1.57 (.062)	3.25 (.128)	2.94 (.116)	N/A	N/A	OST, OSTW, HST, HSTW, GST, UST, USTW, HFSTW, OGP, OTP, NOX, NHX, NHHX, UHX
(*)B-OST-CR062-(**)	1	1.65 (.065)	3.25 (.128)	2.94 (.116)	N/A	N/A	
(*)B-OST-CR2.0MM-(**)	1	2.05 (.081)	3.25 (.128)	2.94 (.116)	N/A	N/A	
(*)B-OST-CR093-(**)	1	2.43 (.096)	3.25 (.128)	4.69 (.185)	N/A	N/A	
(*)B-OST-CR3.0MM-(**)	1	3.09 (.122)	3.96 (.156)	4.69 (.185)	N/A	N/A	
(*)B-OST-CR125-(**)	1	3.25 (.128)	3.96 (.156)	4.69 (.185)	N/A	N/A	
(*)B-OST-CR4.5MM-(**)	2	4.59 (.181)	4.36 (.172)	6.35 (.250)	5.33 (.210)	1.77 (.070)	OST, OSTW, HST, HSTW, GST, UST, OGP, HFSTW, USTW, OTP, NOX, NHX, NHHX, UHX
(*)B-OST-CR188-(**)	2	4.85 (.191)	4.36 (.172)	6.35 (.250)	5.33 (.210)	1.77 (.070)	
(*)B-OST-CR5.5MM-(**)	2	5.58 (.220)	4.36 (.172)	7.87 (.310)	5.33 (.210)	1.77 (.070)	
(*)B-OST-CR6.0MM-(**)	2	6.09 (.240)	4.36 (.172)	7.87 (.310)	5.33 (.210)	1.77 (.070)	
(*)B-OST-CR250-(**)	2	6.42 (.253)	4.36 (.172)	7.87 (.310)	5.33 (.210)	1.77 (.070)	
(*)B-DTC-CR250-(**)	3	6.09 (.240)	N/A	7.87 (.310)	N/A	N/A	DTC
(*)B-DST-CR6.0MM-(**)	3	6.42 (.253)	N/A	7.87 (.310)	N/A	N/A	

Ordering Example: SB-OST-CR250-100, pkg of 100 crimp style stainless steel bushing for 0.250" diameter probe.

(*) Insert "B" for brass or "S" for stainless steel.

(**) Insert quantity: "10" or "100".

CR number indicates compatible probe diameter.

To order crimping tool for use with these bushings, specify model number **BB-OST-CT**.

Accessories for Cable Clamp Caps

Use with OSTW Standard Size Ultimate Connectors

Clamp Grommets Silicone 0.25" Long



Model No.	Inside Dia mm (inch)	Outside Dia mm (inch)	Length mm (inch)	Compatible Connectors
SSRT-CC-018-(*)	3.18 (0.125)	4.77 (0.188)	6.35 (0.250)	OSTW-CC male or female
SSRT-CC-332-(*)	2.38 (0.094)			
SSRT-CC-116-(*)	1.59 (0.063)			
SSRT-CC-132-(*)	0.79 (0.032)			

*Insert pkg quantity: select from 5, 10, 50, 100.

Center number denotes grommet inside diameter for 0.75" long strain relief tubing

OST-CC-TOOL shown smaller than actual size.



All assembly completed from top side.
Prep wire: Straight strip no loop necessary
1st: Load back plate and connector body
2nd: Terminate wire
3rd: Tighten 4 captive screws

Assembly Tool

Model No.	Compatible Connectors
OST-CC-TOOL	OST male or female
SMP-CC-TOOL	SMP male or female

