

SHOCK101-EB

TRI-AXIAL SHOCK DATA LOGGER WITH EXTENDED BATTERY LIFE



Features

- High speed download (115,200 baud)
- Built-in accelerometers
- Real-time operation
- Low cost
- Programmable start time
- Reusable
- Compact
- User-friendly
- CE compliant

Applications

- Shipment monitoring
- Assembly line monitoring
- Brake testing
- Fragility testing
- Laboratory drop testing
- Aircraft turbulence measurement
- Machinery monitoring

The Shock101-EB is a battery powered, stand alone 3-axis shock recorder which offers a battery life of up to 60 days typical. The unit measures and records shock as the peak acceleration levels over the user defined interval.

The Shock101-EB is specifically designed for documenting dynamic environments such as moving vehicles, trucks, containers, ships, etc.

The device is also valuable in characterizing environments such as production and assembly lines of delicate equipment, IC fabrication, communications and computer components.

This is an all-in-one compact, portable, easy to use device that will measure and record up to 349,525 measurements per axis. The storage medium is non-volatile solid state memory, providing maximum data security even if the battery becomes discharged. The user can start and stop directly from the computer and it's small size allows it to fit almost anywhere. The Shock101-EB makes data retrieval quick and easy. Simply plug it into an empty USB port and our user-friendly software does the rest.



MADGETECH DATA LOGGER SOFTWARE

Key

- A** Graph View
- B** Tabular Data View
- C** Statistics
- D** Digital Calibration
- E** Copy to Excel®



Software Features:

- Multiple graph overlay
- Statistics
- Digital calibration
- Zoom in/ zoom out
- Lethality equations (F0, PU)
- Mean Kinetic Temperature
- Full time zone support
- Data annotation
- Min./Max./Average lines
- Data table view
- Automatic report generation
- Summary view
- Multilingual

SHOCK101-EB SPECIFICATIONS*

Channels: Shock (3 axes)				
Acceleration Range (g):	±5	±50	±100	±250
Calibrated Accuracy (g):	±0.2	±1	±2	±4
Acceleration Resolution (g):	0.01	0.05	0.1	0.2
Absolute Max. Acceleration: 250g (all versions)				
Sample Rate: 1.953ms/512Hz				
Reading Interval: 64Hz to 5min				
Memory: 349,525 readings per axis, 1,398,100 total readings				
Start Modes: Software programmable immediate start or delay starts up to 180 days in advance				
Status Indicators: Red: Blinks to indicate sleep mode Red & Green: Blinks to indicate delay start Green: Blinks to indicate taking sample (blinks at sample rate)				
Password Protection: An optional password may be programmed into the device to restrict access to configuration options. Data may be downloaded without the password				
Real Time Recording: Record instantaneous acceleration in real time (1 second or slower reading rate)				

Calibration: Digital calibration through software	
Calibration Date: Automatically recorded within device	
Battery Type: 6 D-cell alkaline batteries included; user replaceable	
Battery Life: 60 days typical @25 °C, 1 minute reading rate	
Data Format: Date and time stamped gravities (g and mg)	
Time Accuracy: ±1 minute/month (at 20 °C, RS232 port not in use)	
Computer Interface: USB (interface cable required); 115,200 baud	
Software: XP SP3/Vista/Windows 7/Windows 8	
Operating Environment: -20 °C to +54 °C, 0 to 95%RH non-condensing	
Dimensions: 5.5" x 5.4" x 3.2" (140 mm x 137 mm x 80 mm)	
Weight: 5 lbs (2.3 kg)	
Materials: Anodized aluminum	
Approvals: CE	

BATTERY WARNING: DISCARD USED BATTERY PROMPTLY. KEEP OUT OF REACH OF CHILDREN. DO NOT DISPOSE OF IN FIRE, RECHARGE, PUT IN BACKWARDS, DISASSEMBLE, OR MIX WITH OTHER BATTERY TYPES. MAY EXPLODE, FLAME OR LEAK AND CAUSE PERSONAL INJURY.

ORDERING INFORMATION

MODEL	DESCRIPTION
SHOCK101-5-EB	±5g Tri-Axial Shock Recorder with extended battery
SHOCK101-50-EB	±50g Tri-Axial Shock Recorder with extended battery
SHOCK101-100-EB	±100g Tri-Axial Shock Recorder with extended battery
SHOCK101-250-EB	±250g Tri-Axial Shock Recorder with extended battery
IFC200	Software, manual and USB interface cable
Calibration Certificate	Calibration Certificate available for data logger
MN1300	Replacement battery for Shock101-EB

ASK ABOUT OUR OTHER DATA LOGGERS

- Temperature
- Humidity
- Pressure
- pH
- Level
- Shock
- LCD Display
- Pulse/Event/State
- Current
- Voltage
- Wireless
- Intrinsically Safe
- Spectral Vibration
- Motion