

Display Temperature Data Logger



Specifications

Alarm Type: Audio/Visual on High/Low Temp Limits

Ambient Operating RH Conditions : 0-95% RH non-condensing (Logger only)

Ambient Operating Temperature Conditions: -4 to 158F (-20 to 70C)

Approvals: CE

Battery Backup: Yes, with use of AC Adapter

Battery Life (Avg): 6 Months

Cable Details: USB - Male Series A plug to 5 pin Male Series B mini plug. Serial - 9 pin female D-shell to male 2.5mm stereo plug

Cable Length: 6ft

Calibration Options: N100, N300, N400, N520

Channels: CH1: Temperature

Data Capacity: 32,000

Dimensions: 1.6 x 3 x 4in

Display Dimensions Height: 1.375

Display Dimensions Width: 2.0

Display Resolution: 0.1 from 0.0 to 999.99; 1 over 1000

Display Type: LCD

Display Update Rate: 10 Seconds (Battery Power), 1 Second (AC Power)

Download Time: 1 Minute (USB), 3 Minutes (Serial)

Download Type: USB / Serial / Flash Card

IP Rating: 20

Included Accessories: Four AA Batteries, Quick Start Guide and RTD Probe. *Software is not included.

Memory Type: EEPROM, Removable Flash Storage Device

Minimum Software Version Required: 9.0

Mounting Options: Wall Mount (With Keyhole)

Network Connectivity: MP100

PC Requirements: Microsoft Windows 98 or better; 16 MB RAM, 1 free USB root hub, CD drive, VGA monitor or better

Power Source: Four AA Batteries (User Replaceable) *AC Adapter is not included, but can be used.

Power Source Notes: AC Power is optional, but not included.

Power Status Indicator: LCD Display

Probe Cable: .110 inch diameter (cord only); .190 inch (probe tip only)

Probe Tip Length: 2inch

Remote Sensor Length: 6

Remote Sensor Type: Platinum RTD Probe

Response Time: 30 Seconds to 63% of Full Scale

Sample Interval: User Selectable (from 1 second to 24 hour intervals, in 1 or 10 second increments).

Software Options: A015, A016, A025, A026

Temperature Accuracy: +/-0.5F from -50 to 350F (+/-0.28C from -46 to 176C)

Temperature Range: -50 to 350F (-45 to 176C)

Temperature Sensor Type: Thermistor/RTD Probe

Unit Weight: 3 lbs
Units/Pkg: 1
Warranty: 12-Month Limited

Accessories SM420



Software

DicksonWare Software with USB Cable



Secure Software

DicksonWare Secure Software with USB Cable



Certificate of Validation

Certificate of Validation



Serial Download Cable

Serial Download Cable - length 6 feet (2m)



USB Download Cable

USB Download Cable - length 6 feet (2m)



AA Batteries

4 Pack AA Lithium Batteries

**Memory Card**

Removable Flash Memory Card

**Card Reader Kit**

Includes USB Reader and Flash Memory Card

**AA Battery**

AA Alkaline Battery

**Universal Plug Kit for AC Adapter**

Set of Three International Power Plugs for AC Adapter

**AC Adapter**

AC Adapter

**Calibration Software**

Logger Calibration Software

Accessories SM420



AC Adapter Extension Cable
10' Power Extension for AC Adapter

Calibrations

N100 1-Point NIST Traceable Calibration

N300 3-Point NIST Traceable Calibration

N400 3-Point Ultima NIST A2LA Accredited Calibration