



Digital Non-Contact Tachometer



Functions

- Up to 99,999 RPM

Features

- Selectable velocity units for contact measurements
- Data hold
- Auto power off
- Low battery indicator
- Removable head
- 2 to 11.8 measuring distance from target
- 1-Year limited warranty

Applications

- Non-contact RPM measurement
- Contact tip measurement
- Contact wheel measurement





Includes

- Battery (9V)
- Manual
- Cone and funnel contact tips
- Reflective tape (non-contact mode) (ART1)

Specifications

Measuring Range	Resolution
10.000~99999 RPM	0.001/0.01/0.1/1
1.0000~9999.9 M/MIN	0.0001/0.001/0.01/0.1
3.0000~30000 FT/MIN	0.0001/0.001/0.01/0.1
1.0000~10000 YD/MIN	0.0001/0.001/0.01/0.1
Accuracy	±(0.1% of rdg. + 2 digits)
Measuring distance	2"~11.8" (5~30cm) from target (Non-contact RPM)
Time base	4.0Mhz Quartz Crystal
Sampling time	1 sec. (>60rpm) >1 sec. (10~60rpm)
Operating Temperature	0~50°C (32~122°F)
Operating Humidity	Max. 80% RH.
Power Supply	9V battery
Power Consumption	5µA (Idle) 18mA (Measurement)

Downloads



Manual



Data Sheet

H28-013



Made in TAIWAN

USA