



FLIR TG167

Spot Thermal Camera

The FLIR TG167 Spot Thermal Camera bridges the gap between single spot infrared thermometers and FLIR's legendary thermal cameras. Equipped with FLIR's exclusive Lepton® micro thermal sensor, the TG167 lets you see the heat so you know where to reliably measure it. Designed for indoor electrical inspection, the TG167 will help you easily find unseen hot and cold spots in electrical cabinets or switch boxes, giving you quality image detail on even small connectors and wires. Then you can store images and download data to show customers and include in reports.

See the Heat™ - Speed Electrical Troubleshooting.

FLIR's Innovative Lepton® IR Imaging Engine

- Instantly shows what's hot and where to aim
- Eliminates blind guesswork
- 24:1 spot size ratio for safer distance measuring

Grab and Go Simplicity.


Fire It Up and Get to Work in Seconds

- Intuitive to operate with no special training required
- Easily save images and data for documentation
- Download images fast over USB or from removable micro SD


Rugged and Reliable.

Designed for the Harshest Environments

- Built to withstand a 2 meter drop
- Covered by FLIR's exclusive 2-10 warranty
- Compact and durable to easily stow in a crowded tool bag



Electrical Troubleshooting



Mechanical Overheating

Specifications

Imaging and optical data	
IR resolution	80 × 60 pixels
Thermal sensitivity/NETD	< 150 mK
Field of view (FOV)	25° × 19.6°
Minimum focus distance	0.1 m (4 in.)
Distance to spot ratio	24:01:00
Image frequency	9 Hz
Focus	Focus free
Detector type	Focal plane array (FPA), uncooled microbolometer
Spectral range	8–14 μm
Display	2.0 in. TFT LCD
Object temperature range	–25 to +380°C (–13 to +716°F)
Accuracy	±1.5% or 1.5°C (2.7°F)
Minimum measurement distance	26 cm (10 in.)
Center spot	Yes
Color palettes	Hot Iron, Rainbow, Grayscale
Memory type	Micro SD card
Image storage capacity	75 000 pictures with included 8 GB Micro SD card
Memory expansion	32 GB SD card maximum
Saved image format	Bitmap (BMP) image with temperature and emissivity
Laser	Dual diverging lasers indicate the temperature measurement area, activated by pulling the trigger
General	
Battery type	Rechargeable Li ion battery
Battery voltage	3.7 V
Battery operating time	>5 hours of continuous scanning with lasers
Battery charge life	30 days minimum
Camera weight, incl. battery	0.312 kg (11 oz.)
Camera size (L × W × H)	186 mm × 55 mm × 94 mm (7.3 in. × 2.2 in. × 3.7 in.)
Tripod mounting	1/4 in.-20 on handle bottom
Includes	Wrist strap lanyard, 8 GB Micro SD card, power supply with separate USB cable, printed documentation