

VACUUM PUMP

A3-COMPATIBLE

Vacuum Pump VP833

Travel light with one pump for A3, A2L and A1

- 8 CFM for fast evacuation
- Works with all common A3, A2L and A1 refrigerants
- Class I, Division 2 Hazardous Locations certified for safe use with flammable A3 refrigerants
- 4 in-line ports for easy hose access and connection
- Rated for 15 microns ultimate vacuum
- Rugged and lightweight with a stable base for easy carry and transport



RUNQUICK® OIL CHANGE SYSTEM

The revolutionary RunQuick® Oil Change System allows lightning-fast, 20-second oil changes while the pump is running and without losing vacuum.

Massive, backlit window lets you clearly see the oil condition to maintain peak efficiency.



Specifications

Flow Rate:	8 CFM
Port Sizes:	(1) 1/4", (2) 3/8", (1) 1/2"
For Use With:	A3, A2L, and A1 Refrigerants
Not For Use With:	R-702, R-717 Refrigerants
Safety Certification:	Class I, Division 2, Groups A, B, C and D T4 23°F (-5°C) ≤ TAMB ≤ 122°F (50°C)
Ultimate Vacuum:	15 Microns
Compressor:	Rotary Vane, Two Stage
Motor:	3/4 HP Brushless DC, 2500 RPM
Dimensions:	7.9 inch x 11.7 inch x 16.0 inch (201 mm x 296 mm x 406 mm)
Weight Empty:	29 lb / 13 kg
Operating Temperature:	23°F to 122°F (-5°C to 50°C)
Included:	2 x 8oz Vacuum Pump Oil Bottles

