

...setting the standard
again and again®

Benchtop Meters — pH/Ion

pH/Ion

Ion 2700 Meter

Measures pH, mV, and ion concentration—well-suited for environmental, water, and food analysis

Takes up less bench space – Overall footprint is nearly 40% smaller than other benchtop meters

Oversized liquid crystal display with bright backlighting – Easier viewing under all lighting conditions

Dynamic reading stability indication shows when you when your measurement is stable – Eliminates guesswork from unstable readings

Up to 500 point nonvolatile memory with time-and-date stamp – Meets GLP requirements

Bidirectional RS-232 – For easy data transfer to your computer

Calibration documentation – Allows you to display, download, or print out calibration details like date and time, buffer values, offset, and slope

Cal-due alarms – Visual and audible reminders when recalibration is needed

Audible out-of-range alarms – Indicate when a reading is above or below a user-settable range

Electrode status – Provides the diagnostics needed to determine when electrode service or replacement is needed

Password protection – Prevents unauthorized setup and calibration



Software included



ISO9001:2008
CERTIFIED SUPPLIER

3 year
warranty
meter only

Specifications

Mode	pH	mV	ISE	Temperature
Range	–2.000 to 20.000 pH	±2000.0 mV	0.001 to 19,999 ppm	0.0 to 100.0°C (32.0 to 212°F)
Resolution	0.001, 0.01, 0.1 pH	0.1 mV	2 or 3 digits	0.1°C or °F
Accuracy	±0.002 pH	±0.2 mV	±0.5% full scale (monovalent), ±1% full scale (divalent)	±0.3°C (±0.5°F)
Calibration	Up to 6 (USA, NIST, DIN, or custom buffer sets)	Offset up to +150 mV	Up to 8 points	—
Connectors	BNC	BNC	BNC	2.5 mm phono

Temperature compensation: manual or automatic from 0 to 100°C (32 to 212°F)

Memory: up to 500 data sets

Output: RS-232, 9-pin female

Display: 3¼" x 2½" (8.3 x 6.2 cm) graphic LCD with backlight

Operating temperature: 0 to 50°C (32 to 122°F), noncondensing probe

Power: universal 110/240 VAC, 50/60 Hz with adapter; UL/CSA listed

Dimensions

Meter: 6⅞" x 6⅞" x 2¼" (15.5 x 17.5 x 6.9 cm)

Boxed: 12" x 9" x 5" (30.8 x 15.5 x 12.4 cm)

Weight

Meter only: 1.4 lb (0.6 kg); **Boxed:** 4 lb (1.8 kg)

Ordering Information

Catalog number	Precalibrated catalog number	Description	Included
WD-35421-02	WD-35421-03	Ion 2700 meter	Meter, electrode holder, and AC adapter
WD-35421-00	WD-35421-01	Ion 2700 meter kit	Meter, pH electrode 35805-04, ATC temperature probe 35613-13, 60-mL of electrode fill solution, electrode holder, and AC adapter

Accessories

WD-35805-04 Replacement combination pH electrode, double-junction, glass body, refillable

WD-35420-01 RS-232 data cable

WD-35630-53 USB data cable


WD-35420-50 Portable printer



Unstable reading is faded.



Reading turns solid when stable.



Calibration documentation can be printed as needed.