

...setting the standard
again and again®

Handheld Meters — Multiparameter

PCD 650 pH/Conductivity/ Dissolved Oxygen Meter

All three parameters, plus temperature, measured and displayed simultaneously!

Durable waterproof and dustproof design with IP67 rating – Even with no probes attached

Push-button calibration for all parameters – 6 points each for pH and conductivity; 3 points for DO

Large back-light graphic display – Multiline display with electrode status indicator, calibration data, and more

User-settable “calibration due” alarm – Out-of-date or unperformed calibrations are now things of the past!

Built-in real-time clock – Time-and-date stamping meets Good Laboratory Practice (GLP) standards

Store up to 500 data sets – Infrared IrDA wireless technology makes PC downloading convenient and easy

Set point alarms – Audible warning when readings are outside set points limit

Research-grade accuracy – Resolution to 0.001 pH and accuracy to ± 0.002 pH

Electrode status indicator – Calibration data provides electrode diagnostic tool

Password protection – Security for calibration and setup menus

Rugged rubber boot – Protects meter from impact (optional; included with kit)



ISO 9001:2008
CERTIFIED SUPPLIER



3 year
warranty
meter only

Specifications

Model	PCD 650 meters
Range	pH
	–2.000 to 20.000 pH
	Ion
	0.001 to 19,900 ppm, molar, or mg/L
	mV
	± 2000 mV
	Conductivity
	0 to 500.0 mS
Resolution	TDS
	0 to 500 ppt
	Salinity
	0 to 80 ppt
	Resistivity
	0 to 20.00 M Ω
	DO
	0.00 to 90.00 mg/L (ppm), 0.0 to 600.0%
Accuracy	Temperature
	–10.0 to 110.0°C (14.0 to 230.0°F), selectable
	pH
	0.1/0.01/0.001 pH
	Ion
	2 or 3 digits
	mV
	0.1 mV
Calibration	Conductivity
	± 0.05 % full-scale
	DO
	0.01 mg/L (ppm), 0.1%
	Temperature
	0.1°C (0.1°F)
	pH
	± 0.002 pH
Accuracy	Ion
	± 0.5 % full-scale (monovalent); ± 1 % full scale (divalent)
	mV
	± 0.2 mV
	Conductivity
	± 1 % full-scale
	DO
	± 0.2 mg/L; ± 2 %
Calibration	Temperature
	± 0.5 °C (± 0.9 °F)
	pH
	Up to 6 buffer values (select from 4 sets): USA 1.68, 4.01, 7.01, 10.01, 12.45; NIST: 1.68, 4.01, 6.86, 9.18, 12.45; DIN: 1.09, 2.06, 4.65, 6.79, 9.23, 12.75, or custom buffers
	Ion
	Up to 6 points
	Conductivity
	Manual up to 5 points (1 per range); automatic up to 4 points (84.0 μ S/cm; 1413 μ S/cm; 12.88 mS/cm, 111.8 mS/cm)
	DO
	Two points; 100% and 0%
Calibration	Temperature
	Offset 0.1°C (0.1°F) increments

TDS factor: 0.40 to 1.00

Cell constant: 0.100 to 10.000

DO salinity correction

Range: 0.0 to 50.0 ppt

Resolution: 0.1 ppt

DO pressure correction

Range: 500 to 1499 mm Hg, 66.6 to 199.9 kPa

Resolution: 1 mm Hg, 0.1 kPa

Memory: up to 500 sets with GLP date and time

Output: infrared, IrDA

Real-time clock: time-and-date stamp on calibration and stored data

Temperature normalization: 15 or 30°C

Temperature coefficient: linear or pure

Temperature compensation: automatic or manual (selectable) from 0 to 100°C

Ambient operating temperature: 0 to 50°C (32 to 122°F)

Power: four 1.5 V AA batteries (included) or optional universal AC adapter, up to 200 hours continuous use

Dimensions

Meter: 7¼" L x 3¼" W x 2¼" H (18.4 x 8.3 x 5.7 cm)

Boxed: 9¼" L x 9¼" W x 2¾" H (23 x 23 x 7 cm)

Weight

Meter: 1 lb (0.5 kg); Boxed: 2 lb (0.9 kg)



Multiprobe holder makes it easy to manage probes simultaneously.



Use multiprobe flow block 35434-90 for groundwater sampling. Holds two 12-mm diameter pH, ORP, or ISE probes, one Oakton conductivity/TDS probe, and one Oakton dissolved oxygen probe.

Ordering Information

Catalog number	Precalibrated catalog number	Description	Included
WD-35434-02	WD-35434-03	PCD 650 meter only	Meter and batteries
WD-35434-00	WD-35434-01	PCD 650 meter	Meter, pH electrode 35816-77, conductivity cell 35408-57, DO probe 35640-50, and batteries
WD-35434-70	WD-35434-71	PCD 650 meter kit	Meter, pH electrode 35816-77, conductivity cell 35408-57, DO probe 35640-50, calibration standards (60 mL each of pH 4.01, pH 7.00, 1413 μ S/cm, and 12.88 mS solution), multiprobe holder, rubber boot, hard carrying case, and batteries

WD-35816-77 pH electrode: double junction, epoxy body, 10-ft (3-m) cable with BNC connector

WD-35418-05 ATC probe. Use for temperature compensation with any pH electrode without built-in ATC

WD-35408-57 Conductivity cell, 2-electrode, K = 1

WD-35640-50 DO probe with 10-ft (3-m) cable

WD-35434-85 Multiprobe holder. Holds one each pH, conductivity, DO, and temperature probes

WD-35434-90 Multiprobe flow block for groundwater sampling

WD-35418-83 Optional adapter, 110/220 VAC

Multiparameter