

...setting the standard  
again and again®

# Handheld Meters — Dissolved Oxygen

## DO 600 Meter

**Fast dissolved oxygen measurement  
with automatic pressure compensation**

**Durable waterproof and dustproof design with IP67 rating** – Even with no probes attached

**Single or multipoint calibration** – Fast, trouble-free calibration in air

**Large backlit graphic display** – Multiline display with electrode status indicator, calibration data, and more

**User-settable “calibration due” alarm** – Out-of-date or unperformed calibrations are now a thing of the past!

**Built-in real-time clock** – Time-and-date stamping meets Good Laboratory Practice (GLP) standards

**Advanced data management** – Store up to 500 data sets and download via IrDA wireless interface

**Set point alarms** – Audible warning when readings are outside set points limit

**No meter warm-up required** – Galvanic probe design lets you take measurements immediately without the typical 15-minute wait!

**Password protection** – Security for calibration and setup menus

**Rugged rubber boot** – Protects meter when out in the field



35441-02

ISO9001:2008  
CERTIFIED SUPPLIER



3 year  
warranty  
meter only

### Specifications

Mode	mg/L (ppm)	% Saturation	Temperature
<b>Range</b>	0.00 to 90.00 mg/L (ppm)	0.0 to 600.0%	0.0 to 50.0°C (32.0 to 122.0°F)
<b>Resolution</b>	0.01 mg/L (ppm)	0.1%	0.1°C (0.1°F)
<b>Accuracy</b>	±0.2% mg/L (ppm)	±2% full-scale	±0.3°C (±0.3°F)

**Temperature compensation:** automatic or manual (selectable) from 0 to 50°C

**Salinity correction**

Range: 0.0 to 50.0 ppt  
Resolution: 0.1 ppt  
Method: key in manually for meter calculation correction

**Barometric pressure correction**

Range: 450 to 825 mm Hg, 59.9 to 109.9 kPa  
Resolution: 1 mm Hg, 0.1 kPa  
Method: automatic correction

**Probe:** galvanic

**Memory:** up to 500 sets with GLP date and time

**Output:** infrared, IrDA

**Real-time clock:** time-and-date stamp on calibration and stored data

**Display:** multiline LCD with backlighting

**Ambient operating temperature:** 0 to 50°C (32 to 122°F)

**Power:** four 1.5 V AA batteries (included) or optional universal AC adapter, up to 500 hours continuous use

**Dimensions**

**Meter:** 7¼" L x 3¼" W x 2¼" H (18.4 x 8.3 x 5.7 cm)  
**Boxed:** 9½" L x 9½" W x 2¾" H (23 x 23 x 7 cm)

**Weight**

**Meter:** 1 lb (0.5 kg); **Boxed:** 2 lb (0.9 kg)



Complete kit available; includes meter, solutions, rubber boot, and carrying case.

DO probes available with up to 100-ft (30-m) cable. See page 50 to order.

### Ordering Information

Catalog number	Precalibrated catalog number	Description	Included
WD-35441-02	WD-35441-03	DO 600 meter only	Meter and batteries
WD-35441-00	WD-35441-01	DO 600 meter	Meter, probe 35640-50 with 10-ft (3-m) cable, electrolyte solution, replacement membrane caps, and batteries
WD-35441-70	WD-35441-71	DO 600 meter kit	Meter, probe 35640-50 with 10-ft (3-m) cable, electrolyte solution, rubber boot, replacement membrane caps, hard carrying case, and batteries

WD-35640-50 Replacement dissolved oxygen probe, 10-ft (3-m) cable

WD-35418-83 Optional adapter, 110/220 VAC

WD-35418-86 Protective rubber boot for all 600- and 650-series meters

Dissolved Oxygen