

pH 5+ and 6+ Meters

Rugged, compact meters offer high accuracy at an extremely affordable price!

Simple push-button operation – So fast and easy, anyone can use it

Toggle between pH and temperature in °C with a press of a button

Five-point pH calibration – Choose from standard US, NIST, and pure water; gives you high ± 0.01 pH accuracy

Auto buffer recognition – Automatically identifies the correct pH buffer for rapid calibration

Calibration instructions are printed on back of meter – For quick reference and added convenience

Automatic temperature compensation (ATC) – For the highest accuracy in changing temperature conditions

Hold and Auto-off functions

Built-in stand for benchtop or long-term use

Protective boot – Helps shield your meter from drops and dings

Meter kits available – Contain everything you need for calibration and measurement packaged in a hard carrying case – the best option.

pH 6+ also features

Measurements in pH, mV, and °C – Use for ORP (Redox) measurements



35613-52

ISO 9001:2008
CERTIFIED SUPPLIER

3 year
warranty
meter only

Specifications

| Model | pH 5+ and pH 6+ meters | | pH 6+ meter only |
|--------------------|--|-------------------------|------------------|
| Mode | pH | Temperature | mV |
| Range | 0.00 to 14.00 pH | 0.0 to 100.0°C | ± 1000 mV |
| Resolution | 0.01 pH | 0.1°C | 1 mV |
| Accuracy | ± 0.01 pH | $\pm 0.5^\circ\text{C}$ | ± 2 mV |
| Calibration | Up to 5 buffer values: choose from standard US, NIST, and pure water buffer values | Offset 0.1°C increments | ± 20 mV |

Temperature compensation:
automatic from 0.0 to 100.0°C
Operating temperature: 0 to 50°C (32 to 122°F)
Power: four 1.5 V AAA batteries (included),
>200 hours continuous use

Dimensions
Meter: 5½"L x 2¾"W x 1¾"H (14 x 7 x 3.5 cm)
Boxed: 9¼"L x 6½"W x 3"H (23.5 x 16.5 x 7.5 cm)
Weight
Meter: 0.9 lb (0.4 kg); **Boxed:** 1 lb (0.5 kg)

Ordering Information

| Catalog number | Precalibrated catalog number | Description | Included |
|----------------|------------------------------|-------------------------|---|
| WD-35613-50 | WD-35613-51 | pH 5+ meter only | Meter, ATC probe, protective rubber boot, and batteries |
| WD-35613-20 | WD-35613-41 | pH 6+ meter only | |
| WD-35613-52 | WD-35613-53 | pH 5+ meter with probes | Meter; single-portion, epoxy-body pH electrode; ATC probe; protective rubber boot; and batteries |
| WD-35613-22 | WD-35613-42 | pH 6+ meter with probes | |
| WD-35613-54 | WD-35613-55 | pH 5+ meter kit | Meter; "All-in-One" single-portion, epoxy-sealed pH electrode; pH buffer pouches (pH 4.01, 7.00, 10.00, and rinse water); sample bottles; protective rubber boot; batteries; and hard carrying case |
| WD-35613-24 | WD-35613-44 | pH 6+ meter kit | |

Accessories

WD-35804-00 Replacement pH electrode
WD-35811-71 Replacement "All-in-One" single-portion, epoxy-sealed pH electrode
WD-35613-05 Replacement ATC probe



Meters include protective rubber boot and a built-in stand.