

Temperature

Digi-Sense® Sentry Table/Wall-Mount Thermometers

Get high, low, and current temperatures

– Monitor temperature continuously

Thermometers include a weatherproof remote sensor with a 10-ft (3-m) long, 1/16"-diameter micro cable. Unplug external probe to monitor ambient temperature. Large LCD updates every 10 seconds, and a simple one-button reset to clear the high/low memory.

Refrigerator/freezer models are supplied with the temperature sensor enclosed in a

glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Models 94460-96, -97 have the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

What's included: mounting hardware, one battery, and NIST-traceable calibration report supplied by manufacturer. 



[GH-17101-61](#) NIST-traceable recalibration with data for digital indicator

Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F	1°F	±1°F	GH-94460-76	
		-50 to 70°C	1°C	±1°C	GH-94460-77	
Refrigerator/freezer	Bottle probe	-58 to 158°F	1°F	±1°F	GH-94460-86	
		-50 to 70°C	1°C	±1°C	GH-94460-87	
Refrigerator/freezer	5-mL bottle probe	-58 to 158°F	1°F	±1°F	GH-94460-96	
		-50 to 70°C	1°C	±1°C	GH-94460-97	

Digi-Sense® Jumbo-Display Table/Wall-Mount Thermometers

Read from 30 feet away

- Triple display simultaneously shows maximum, minimum, and current probe temperatures
- Min/max monitors high/low readings overnight, weekends or for any time period
- Alarm alerts when temperature rises above or falls below a set point

Refrigerator/freezer model 94460-82 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-83 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

What's included: Velcro® and magnetic strips, AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer. 



Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F	0.1°	±1°	GH-94460-81	
Refrigerator/freezer	Bottle probe	(-50 to 70°C)			GH-94460-82	
Refrigerator/freezer	5-mL bottle probe				GH-94460-83	

[GH-09376-00](#) Replacement batteries, AAA. Pack of 12

[GH-17101-61](#) NIST-traceable recalibration with data for digital indicator

Digi-Sense® High-Accuracy Table/Wall-Mount Thermometers

Don't be caught off guard

- Alarm provides alert when temperature rises above or falls below a set point

Display simultaneously shows maximum, minimum, and current probe temperatures. Min/max monitors high/low readings for any time period. Model 94460-74 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-73 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

What's included: Velcro® and magnetic strips, one AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer. 



Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F	0.1°	±0.5°	GH-94460-88	
Refrigerator/freezer	Bottle probe	(-50 to 70°C)			GH-94460-74	
Refrigerator/freezer	5-mL bottle probe				GH-94460-73	

[GH-09376-00](#) Replacement batteries, AAA. Pack of 12

[GH-17101-61](#) NIST-traceable recalibration with data for digital indicator