

## Temperature

### Digi-Sense® Sentry Table/Wall-Mount Thermometers

#### Get high, low, and current temperatures

##### – Monitor temperature continuously

Thermometers include a weatherproof remote sensor with a 10-ft (3-m) long, 1/16"-diameter micro cable. Unplug external probe to monitor ambient temperature. Large LCD updates every 10 seconds, and a simple one-button reset to clear the high/low memory.

Refrigerator/freezer models are supplied with the temperature sensor enclosed in a

glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Models 94460-96, -97 have the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** mounting hardware, one battery, and NIST-traceable calibration report supplied by manufacturer.



**GH-17101-61** NIST-traceable recalibration with data for digital indicator

| Application          | Sensor type       | Range        | Resolution | Accuracy | Catalog number              | Price |
|----------------------|-------------------|--------------|------------|----------|-----------------------------|-------|
| General purpose      | Wire probe        | -58 to 158°F | 1°F        | ±1°F     | <a href="#">GH-94460-76</a> |       |
|                      |                   | -50 to 70°C  | 1°C        | ±1°C     | <a href="#">GH-94460-77</a> |       |
| Refrigerator/freezer | Bottle probe      | -58 to 158°F | 1°F        | ±1°F     | <a href="#">GH-94460-86</a> |       |
|                      |                   | -50 to 70°C  | 1°C        | ±1°C     | <a href="#">GH-94460-87</a> |       |
| Refrigerator/freezer | 5-mL bottle probe | -58 to 158°F | 1°F        | ±1°F     | <a href="#">GH-94460-96</a> |       |
|                      |                   | -50 to 70°C  | 1°C        | ±1°C     | <a href="#">GH-94460-97</a> |       |

### Digi-Sense® Jumbo-Display Table/Wall-Mount Thermometers

#### Read from 30 feet away

- Triple display simultaneously shows maximum, minimum, and current probe temperatures
- Min/max monitors high/low readings overnight, weekends or for any time period
- Alarm alerts when temperature rises above or falls below a set point

Refrigerator/freezer model 94460-82 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-83 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** Velcro® and magnetic strips, AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer.



**GH-09376-00** Replacement batteries, AAA. Pack of 12

**GH-17101-61** NIST-traceable recalibration with data for digital indicator

| Application          | Sensor type       | Range                         | Resolution | Accuracy | Catalog number              | Price |
|----------------------|-------------------|-------------------------------|------------|----------|-----------------------------|-------|
| General purpose      | Wire probe        | -58 to 158°F<br>(-50 to 70°C) | 0.1°       | ±1°      | <a href="#">GH-94460-81</a> |       |
| Refrigerator/freezer | Bottle probe      |                               |            |          | <a href="#">GH-94460-82</a> |       |
| Refrigerator/freezer | 5-mL bottle probe |                               |            |          | <a href="#">GH-94460-83</a> |       |

### Digi-Sense® High-Accuracy Table/Wall-Mount Thermometers

#### Don't be caught off guard

- Alarm provides alert when temperature rises above or falls below a set point

Display simultaneously shows maximum, minimum, and current probe temperatures. Min/max monitors high/low readings for any time period. Model 94460-74 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-73 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** Velcro® and magnetic strips, one AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer.



**GH-09376-00** Replacement batteries, AAA. Pack of 12

**GH-17101-61** NIST-traceable recalibration with data for digital indicator

| Application          | Sensor type       | Range                         | Resolution | Accuracy | Catalog number              | Price |
|----------------------|-------------------|-------------------------------|------------|----------|-----------------------------|-------|
| General purpose      | Wire probe        | -58 to 158°F<br>(-50 to 70°C) | 0.1°       | ±0.5°    | <a href="#">GH-94460-88</a> |       |
| Refrigerator/freezer | Bottle probe      |                               |            |          | <a href="#">GH-94460-74</a> |       |
| Refrigerator/freezer | 5-mL bottle probe |                               |            |          | <a href="#">GH-94460-73</a> |       |