

## Temperature

### Digi-Sense® Sentry Table/Wall-Mount Thermometers

#### Get high, low, and current temperatures

##### – Monitor temperature continuously

Thermometers include a weatherproof remote sensor with a 10-ft (3-m) long, 1/16"-diameter micro cable. Unplug external probe to monitor ambient temperature. Large LCD updates every 10 seconds, and a simple one-button reset to clear the high/low memory.

Refrigerator/freezer models are supplied with the temperature sensor enclosed in a

glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Models 94460-96, -97 have the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** mounting hardware, one battery, and NIST-traceable calibration report supplied by manufacturer.



**GH-17101-61** NIST-traceable recalibration with data for digital indicator

Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F	1°F	±1°F	<a href="#">GH-94460-76</a>	
		-50 to 70°C	1°C	±1°C	<a href="#">GH-94460-77</a>	
Refrigerator/freezer	Bottle probe	-58 to 158°F	1°F	±1°F	<a href="#">GH-94460-86</a>	
		-50 to 70°C	1°C	±1°C	<a href="#">GH-94460-87</a>	
Refrigerator/freezer	5-mL bottle probe	-58 to 158°F	1°F	±1°F	<a href="#">GH-94460-96</a>	
		-50 to 70°C	1°C	±1°C	<a href="#">GH-94460-97</a>	

### Digi-Sense® Jumbo-Display Table/Wall-Mount Thermometers

#### Read from 30 feet away

- Triple display simultaneously shows maximum, minimum, and current probe temperatures
- Min/max monitors high/low readings overnight, weekends or for any time period
- Alarm alerts when temperature rises above or falls below a set point

Refrigerator/freezer model 94460-82 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-83 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** Velcro® and magnetic strips, AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer.



Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F (-50 to 70°C)	0.1°	±1°	<a href="#">GH-94460-81</a>	
Refrigerator/freezer	Bottle probe				<a href="#">GH-94460-82</a>	
Refrigerator/freezer	5-mL bottle probe				<a href="#">GH-94460-83</a>	



**GH-09376-00** Replacement batteries, AAA. Pack of 12

**GH-17101-61** NIST-traceable recalibration with data for digital indicator

### Digi-Sense® High-Accuracy Table/Wall-Mount Thermometers

#### Don't be caught off guard

- Alarm provides alert when temperature rises above or falls below a set point

Display simultaneously shows maximum, minimum, and current probe temperatures. Min/max monitors high/low readings for any time period. Model 94460-74 is supplied with the temperature sensor enclosed in a nontoxic glycol-filled bottle, protecting it from rapid temperature changes when refrigerator door is opened. Model 94460-73 has the temperature sensor enclosed in a 5-mL bottle, allowing it to fit into a tray while protecting it from rapid temperature changes.

**What's included:** Velcro® and magnetic strips, one AAA alkaline battery, and NIST-traceable calibration report supplied by manufacturer.



Application	Sensor type	Range	Resolution	Accuracy	Catalog number	Price
General purpose	Wire probe	-58 to 158°F (-50 to 70°C)	0.1°	±0.5°	<a href="#">GH-94460-88</a>	
Refrigerator/freezer	Bottle probe				<a href="#">GH-94460-74</a>	
Refrigerator/freezer	5-mL bottle probe				<a href="#">GH-94460-73</a>	



**GH-09376-00** Replacement batteries, AAA. Pack of 12

**GH-17101-61** NIST-traceable recalibration with data for digital indicator